

GraphSol

SELF ADHESIVE VINYL

Product & Code	GraphSol 5 year Polymeric Gloss Clear Vinyl				
Product Description	With a 80um HQ non flow-mark Vinyl film(glossy), clear high tack acrylic glueVinyl S/A provides good and stable prints, strong adhesion.				
Printing	Eco/ Sol	UV	Latex	Aqueous	Screen
	■	■	□		■
Applications	Adhesive Signages	POP Displays posters	Backlit Displays/ frames	Exhibits, Events signs	Vehicle graphic
	■				
Sizes Available	1.37×50M				
Physical Properties	Face film	80um (3.1mil) calendared monomeric			
	Finish	Glossy			
	Whiteness	Clear			
	Gloss/60deg	70-85			
	Elongation at break	70N/mm			
Adhesive Properties	Adhesive Type	Removable Clear			
	Thickness	≥20 micron (≥0.8 mil)			
	Intial Tack(ASTM D882-02)	≥7#			
	Holding(ASTM D882-02)	≥24			
	180° peel strength(ASTM D882-02)	10~12 N/25mm			
Release Liner	Liner weight	120 g/m ²			
	Liner Type	Single side PE coated silicon paper			
Storage & Application	Shelf Time	60 months			
	Application Temperature	-20 °C to 65 °C (-4 °F to 149 °F)			
	Durability	60 Months			
■ FULLY COMPATIBLE					
□ FAIRLY COMPATIBLE OR NEED TO BE VERIFIED.					

Graphic Solutions Digital cc

Head Office
4 Midhurst Way
Constantia, 7806

Reg. no. CK 1996/003463/23
Vat Reg. 494 015 4919
Tel: 021 794 6094