

# GraphSol

SELF ADHESIVE VINYL

<b>Product &amp; Code</b>	<b>GraphSol 5 year Polymeric White Gloss Blockout Vinyl</b>				
<b>Product Description</b>	With a 80um HQ non flow-mark Vinyl film (glossy), black or grey high tack permanent acrylic glue, Vinyl S/A provides good and stable prints, strong adhesion.				
<b>Printing</b>	<b>Eco/ Sol</b>	<b>UV</b>	<b>Latex</b>	<b>Aqueous</b>	<b>Screen</b>
	■	■	□		■
<b>Applications</b>	<b>Adhesive Signage</b>	<b>POP Displays posters</b>	<b>Backlit Displays/ frames</b>	<b>Exhibits, Events signs</b>	<b>Vehicle graphic</b>
	■				
<b>Sizes Available</b>	1.37×50M				
<b>Physical Properties</b>	<b>Face film</b>	80um polymeric			
	<b>Finish</b>	Glossy			
	<b>Whiteness</b>	91%			
	<b>Gloss/60deg</b>	70-85			
	<b>Elongation at break</b>	70N/mm			
<b>Adhesive Properties</b>	<b>Adhesive Type</b>	Permanent Black/Grey			
	<b>Thickness</b>	≥20 micron (≥0.8 mil)			
	<b>Initial Tack(ASTM D882-02)</b>	≥7#			
	<b>Holding(ASTM D882-02)</b>	≥24			
	<b>180° peel strength(ASTM D882-02)</b>	10~12 N/25mm			
<b>Release Liner</b>	<b>Liner weight</b>	120 g/m <sup>2</sup>			
	<b>Liner Type</b>	Single side PE coated silicon paper			
<b>Storage &amp; Application</b>	<b>Shelf Time</b>	60 months			
	<b>Application Temperature</b>	-20 °C to 65 °C ( -4 °F to 149 °F )			
	<b>Durability</b>	60 Months			
■ FULLY COMPATIBLE					
□ FAIRLY COMPATIBLE OR NEED TO BE VERIFIED.					

Graphic Solutions Digital cc

Head Office  
4 Midhurst Way  
Constantia, 7806

Reg. no. CK 1996/003463/23  
Vat Reg. 494 015 4919  
Tel: 021 794 6094