

GraphSol

SELF ADHESIVE VINYL

GraphSol Glass Etch Printable Window Film

		→	SURFACE MATERIAL
PRODUCTION		→	PRESSURE SENSITIVE ADHESIVE
CONSTRUCTION		→	LINER
SURFACE MATERIAL		LINER	
ARTICLE NAME	PVC FILM	ARTICLE NAME	PE LAMI RELEASE PAPER
mm		g/m^2	
THICKNESS	0.09±0.02	BASIC WEIGHT	100±5
COLOR	Transparent Frosted, Sparkle or Dark	COLOR	WHITE
SOFTNESS	26PHR	$g/15mm$	
PRINT ABILITY	GOOD (Latex Compatible)	TENSION STRENGTH	
WEATHER RESISTANCE	1-3 Years	SMOOTHNESS	GOOD
		DIE CUTTING	GOOD
PRESSURE SENSITIVE ADHESIVE			
		$g/25mm$	
ADHESIVE BASE	ACRYLIC	RELEASE FORCE	7~15
mm		hr/kg*25mm2	
THICKNESS	0.028±0.002	HOLDING POWER	8↑
g/m^2			
DRY COATING WEIGHT	60±2	WEATHER RESISTANCE	1-3 Years
NO/BALL		(°C)	
INITIAL TACK	6↑	TEMPERATURE RANGE	- 3~80
kg/25mm			
180° PEEL ADHESIVE	0.8↑	SOLVENT RESISTANCE	GOOD
REMARK : THE TECHNICAL DATA ARE BASED ON RELIABLE EXPERIMENTS CARRIED OUT BY THE" COMPANY" .WHICH HOWEVER; ARE NOT TO GUARANTEE THOSE PROPER TIES AND CHARACTERISTICS COMPLEXLY AS SPECIFIED THEREIN, KINDLY STUDY YOUR PURPOSE ,CONDITION AND THIS PRODUCT PROPERLY BEFORE APPLICATION.			
All above information shall be only use as a guide. Buyers shall independently test and determine the products suitability.			

Graphic Solutions Digital cc

Head Office
4 Midhurst Way
Constantia, 7806

Reg No. CK 1996/003463/23
Vat no. 494 015 4919
Tel: 021 794 6094