



Mesh 270g without Liner

Items	Value	Unit	Test Method
Base Fabric	Polyester		DIN60001
Both Side Layer	Polyvinyl Chloride		DIN60001
Thickness	0.4	mm	ASTM D-1593
Yarn	1000x1000	D	
Construction	12x12	sq.inch	
Weight	270+-	g/sqm	DIN53352
Weight Tolerance	6.6% difference		
Light Pass	37%		
Aircon	1248mm/s		
Tensile Strength (L)	1500	N/50mm	DIN53354
Tensile Strength (W)	1800	N/50mm	
Tearing Strength (L/W)	450	N/50mm	DIN53363
Tearing Strength (L/W)	500	N/50mm	
Temperature Resistance	-10 ~ + 70	°C	DIN53372
Fire Rating	B2		DIN4102-1
Material Warranty	6 Months		
UV Resistant	Yes		
Mildew Resistant	Yes		

1. Anti-tearing 1000D yarn, woven by Kaermaye wrap knitting equipment form Germany, doubles its strength and ensure great anti-tearing performance. 2. Good ventilation and lighting. 3. Featured by low cost and easy operation. 4. Hole size 1.05mm x 1.05mm

All above information shall only be used as a guide. Buyers shall independantly test and determine the products suitability

Graphic Solutions Digital cc

Head Office
4 Midhurst Way
Constantia, 7806

Reg No. CK 1996/003463/23
Vat no. 494 015 4919
Tel: 021 794 6094