



### White Black White Blockout PVC 600gsm

Items	Value	Unit	Test Method
Base Fabric	Polyester		DIN60001
Coated Layer	Polyvinyl Chloride		DIN60001
Production Method	Polyvinyl Chloride material coat on base fabric, then heat laminated process		
Yarn	1000x100	D	
Construction	12x12	sq.inch	
Weight	600	g/sqm	
Weight Tolerance	6.6% difference		
Tensile Strenth (N/inch)	LENGTH	1500	DIN53354 or HG/T2580
	WIDTH	1500	
Tearing Strength (N)	LENGTH	350	DIN53363 or HG/T2581
	WIDTH	350	
Peeling Strength (N/inch)	82		DIN53357 or GB8808
Temperature Resistance	-20 ~ + 70	° C	DIN53361
Fire Rating	B2		
Material Warranty	6 Months		
UV Resistant	Yes		
Mildew Resitant	Yes		

All the above information should be only used as a guide, buyers should independently test and determine the products suitability. The abovementioned data are averages of the tests and should be used for the purpose of lawsuit of warranty.

Graphic Solutions Digital cc

Head Office  
4 Midhurst Way  
Constantia, 7806

Reg No. CK 1996/003463/23  
Vat no. 494 015 4919  
Tel: 021 794 6094