

# GraphSol

SELF ADHESIVE VINYL

## GraphSol 3yr Gloss White Removable Block Out

| Specification                            | Description  |   |
|--|--|---|
| <b>PVC</b>                               | Type   | PVC Calendered monomeric soft PVC film                |
|  | Thickness  | 80±10um   |
|  | Color Code   | Ceramic white   |
|  | Shrinkage  | ≤0.8%   |
|  | Surface Tension  | ≥30dn/cm  |
|  | Opacity  | >80%  |
| <b>Adhesive</b>                          | Type   | Black solvent based removable pressure sensitive glue |
|  | Weight(g/m <sup>2</sup> )  | 20±2  |
|  | Recommended Service Temperature  | -10°C~65°C  |
|  | 180° Peeling Force   | ≥6N/25mm 20min<br>(GB2792-81 China National Standard) |
|  | Initial Adhesion-Ball Tack   | ≥5# Steel Ball<br>(GB4852-84 China National Standard) |
|  | Holding Power  | ≥800min<br>(GB4854-84 China National Standard)        |
| <b>Liner</b>                             | Type   | Kraft paper   |
|  | Color  | White   |
|  | Weight   | 120g±5g/m <sup>2</sup>                                |
|  | Release Force  | 0.05~0.2N/25mm  |
| <b>Storage Period</b>                    | 12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%  |   |
| <b>Application</b>                       | Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application.   |   |
| <b>Compatibility of printers and ink</b> | Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek and HP Scitex. Inks should be the original ink from the printer manufacturers. The best printing temperature is 35-40°C. |   |

Graphic Solutions Digital (Pty) Ltd

Head Office  
4 Midhurst Way  
Constantia, 7806

Co. Reg No: 2020/459255/07  
Vat Reg No. 494 015 4919  
Tel: +27 21 794 6094 / 8919