

GraphSol

SELF ADHESIVE VINYL

GraphSol 3yr Clear Monomeric SAV Gloss/Matt

Specification	Description	
PVC	Type	PVC Calendered monomeric soft PVC film
	Thickness	80±10um
	Color Code	Clear
	Shrinkage	≤0.8%
	Surface Tension	≥30dn/cm
	Surface Finishing	70-90%
Adhesive	Type	Clear solvent based permanent pressure sensitive glue
	Weight(g/m ²)	25±2
	Recommended Service Temperature	-10°C~65°C
	180° Peeling Force	≥6.5N/25mm 20min (GB2792-81 China National Standard)
	Initial Adhesion-Ball Tack	≥5# Steel Ball (GB4852-84 China National Standard)
	Holding Power	≥800min (GB4854-84 China National Standard)
Liner	Type	Kraft paper
	Color	white
	Weight	130g±5g/m ²
	Release Force	0.05~0.2N/25mm
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application.	
Compatibility of printers and ink	Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek and HP Scitex. Inks should be the original ink from the printer manufacturers. The best printing temperature is 35-40°C.	

Graphic Solutions Digital (Pty) Ltd

Head Office
4 Midhurst Way
Constantia, 7806

Co. Reg No: 2020/459255/07
Vat Reg No. 494 015 4919
Tel: +27 21 794 6094 / 8919