

GraphSol

SELF ADHESIVE VINYL

GraphSol 3yr Glass Etch Printable Window Film

		→	SURFACE MATERIAL	
PRODUCTION		→	PRESSURE SENSITIVE ADHESIVE	
CONSTRUCTION		→	LINER	
SURFACE MATERIAL		LINER		
ARTICLE NAME	PVC FILM	ARTICLE NAME	PE LAMI RELEASE PAPER	
mm		g/m ²		
THICKNESS	0.09±0.02	BASIC WEIGHT	100±5	
COLOR	Transparent Frosted, Sparkle or Dark	COLOR	WHITE	
SOFTNESS	26PHR	g/15mm		
PRINT ABILITY	GOOD (Latex Compatible)	TENSION STRENGTH		
WEATHER RESISTANCE	1-3 Years	SMOOTHNESS	GOOD	
		DIE CUTTING	GOOD	
PRESSURE SENSITIVE ADHESIVE				
		g/25mm		
ADHESIVE BASE	ACRYLIC	RELEASE FORCE	7~15	
mm		hr/kg*25mm ²		
THICKNESS	0.028±0.002	HOLDING POWER	8↑	
g/m ²				
DRY COATING WEIGHT	60±2	WEATHER RESISTANCE	1-3 Years	
NO/BALL	6↑	(°C)		
INITIAL TACK		TEMPER ATURE RANGE	-10 °c~ 65° c	
kg/25mm				
180° PEEL ADHESIVE	0.8↑	SOLVENT RESISTANCE	GOOD	

REMARK : THE TECHNICAL DATA ARE BASED ON RELIABLE EXPERIMENTS CARRIED OUT BY THE "COMPANY" WHICH HOWEVER; ARE NOT TO GUARANTEE THOSE PROPERTIES AND CHARACTERISTICS COMPLEXLY AS SPECIFIED THEREIN, KINDLY STUDY YOUR PURPOSE, CONDITION AND THIS PRODUCT PROPERLY BEFORE APPLICATION. All above information shall be only use as a guide. Buyers shall independently test and determine the products suitability.

Graphic Solutions Digital (Pty) Ltd

Head Office
4 Midhurst Way
Constantia, 7806

Co. Reg No: 2020/459255/07
Vat Reg No. 494 015 4919
Tel: +27 21 794 6094