



**GraphSol 3yr Honeycomb Reflective Vinyl White**

1	Product's Name	Adhesive Crystal Lattice Reflective Film
2	Specifications	Length: 50m Width: 1.24m (There are two types such as release paper and release film available for the release layer)
3	Feature	White glittering luster
4	Application	Reflective advertising material, printing materials, reflective Safety identification and signs.
5	Inverse reflection coefficient of products	The average inverse reflection coefficient exceed $100\text{cd.lx}^{-1}.\text{m}^{-2}$ in the condition of observation angle $0.2^\circ$ and incident angle $-4^\circ$
6	Freeze resistance	5°C for normal material, -10°C for cold-resistant material
7	Weather resistance	3 years for normal outdoor use
8	Water resistance	Crystal lattice overall waterproof, anti permeability
9	Combustion	Self extinguishing
10		<p>① Direct printing by using solvent based inks for printing machine and outdoor photo machine, indoor photo machine and water based ink painting are not allowed</p> <p>② Adjust the height of the nozzle to avoid friction and collision if the thickness of the product is not the same</p> <p>③ Turn down the temperature properly if using the heating and drying device when printing. Don't touch directly by hand to avoid leaving a mark.</p> <p>④ Avoid direct sunlight and chemicals, put in a dry place.</p> <p>⑤ -10 minimum to 65 °C maximum is the optimum temperature for producing, low temperature area pls use the cold resistant material crystal lattice.</p> <p>⑥ The remaining crystal lattice should be packed in good protection to prevent from wrinkle</p> <p>⑦ Manual monitoring is necessary in printing process to prevent from the ink squeegeeing which is caused by</p>
All above information shall be only use as a guide. Buyers shall independently test and determine the products suitability.		

Graphic Solutions Digital cc

Head Office  
4 Midhurst Way  
Constantia, 7806

Reg. no. CK 1996/003463/23  
Vat Reg. 494 015 4919  
Tel: 021 794 6094