

# GraphSol

SELF ADHESIVE VINYL

GraphSol 3yr 100μ SAV HIGH TACK ADHESIVE Matt White

Specification	Description	
<b>PVC</b>	Type	Calendared monomeric soft PVC film
	Thickness	100±10um
	Color Code	Matt white
	Shrinkage	≤1%
	Surface Tension	≥30dn/cm
	Opacity	>75%
<b>Adhesive</b>	Type	Clear solvent based permanent high tack pressure sensitive glue
	Weight(g/m <sup>2</sup> )	35±5
	Recommended Service Temperature	-10°C~65°C
	180°Peeling Force	≥20N/25mm (FTM1)
	Initial Tack	≥13N/25MM*25M (FTM9)
	Holding Power	≥1440min (FTM8)
<b>Liner</b>	Type	PE Kraft paper
	Color	white
	Weight	140g±10g/m <sup>2</sup>
	Release Force	0.05~0.2N/25mm
<b>Storage Period</b>	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
<b>Application</b>	Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application.	
<b>Compatibility of printers and ink</b>	0°C Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek and HP Scitex. Inks should be the original ink from the printer manufacturers. The best printing temperature is 35-40°C.	

**Graphic Solutions Digital (Pty) Ltd**

**Head Office**  
**4 Midhurst Way**  
**Constantia, 7806**

**Co. Reg No: 2020/459255/07**  
**Vat Reg No. 494 015 4919**  
**Tel: +27 21 794 6094 / 8919**