

GraphSol

SELF ADHESIVE VINYL

GraphSol 3yr SUPER Clear PVC Film

Specification	Description	
PVC	Type	Calendared monomeric soft PVC film
	Thickness	100±10um
	Color Code	Super Clear
	Shrinkage	≤0.8%
	Surface Tension	≥30dn/cm
	Opacity	≥95%
Adhesive	Type	Clear solvent based removable pressure sensitive glue
	Weight(g/m ²)	25±5
	Recommended Service Temperature	-10°C~65°C
	Peeling Force	≥8N/25mm (FTM1)
	Initial Tack	≥5N/25MM*25M (FTM9)
	Holding Power	≥2000min (FTM8)
	Removable Durability	One year cleanly removable glue on clean glass, Bakeable paint, stainless surface at temperature of 23-25 C and RH of 50-60% indoor.
Liner	Type	75mic PET
	Color	Clear
	Weight	105±10g/m ²
	Release Force	0.05~0.2N/25MM
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	Indoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application.	
Compatibility of printers and ink	Media is suitable for UV digital printers Inks should be the original ink from the printer manufacturers.	

Graphic Solutions Digital (Pty) Ltd

Head Office
4 Midhurst Way
Constantia, 7806

Co. Reg No: 2020/459255/07
Vat Reg No. 494 015 4919
Tel: +27 21 794 6094 / 8919