

Product & Code	GraphSol 5yr Polymeric White Gloss Blockout Vinyl						
Product Description	With a 80um HQ non flow-mark Vinyl film (glossy), black or grey high tack permanent acrylic glue, Vinyl S/A provides good and stable prints, strong adhesion.						
Printing	Eco/ Sol	UV		Latex	Aqueous	Screen	
	•	-					
Applications	Adhesive Signage	POP Displays posters	D	Backlit Displays/ frames	Exhibits, Events signs	Vehicle graphic	
Sizes Available	1.37×50M					<u> </u>	
Physical	Face film			80um polymeric			
Properties	Finish			Glossy			
	Whiteness			91%			
	Gloss/60deg			70-85			
	Elongation at break			70N/mm			
Adhesive	Adhesive Type			Permanent Black/Grey			
Properties	Thickness			≥20 micron (≥0.8 mil)			
	Initial Tack (ASTM D882-02)			≥7#			
	Holding (ASTM D882-02)			≥24			
	180° peel strength (ASTM D882-02)			10~12 N/25mm			
Release Liner	Liner weight			120 g/m²			
	Liner Type			Single side PE coated silicon paper			
Storage &	Shelf Time			60 months			
Application	Application Temperature			-10 °C to 65 °C			
	Durability			60 Months			
■ FULLY COMPATI	BLE						

Graphic Solutions Digital (Pty) Ltd

Head Office 4 Midhurst Way Constantia, 7806 Co. Reg No: 2020/459255/07 Vat Reg No. 494 015 4919 Tel: +27 21 794 6094 / 8919