

# GraphSol

SELF ADHESIVE VINYL

Product & Code	GraphSol 5yr Polymeric Gloss Clear Vinyl				
Product Description	With an 80um HQ nonflow-mark Vinyl film(glossy), clear high tack acrylic glue Vinyl S/A provides good and stable prints, strong adhesion.				
Printing	Eco/ Sol	UV	Latex	Aqueous	Screen
	■	■	□		■
Applications	Adhesive Signages	POP Displays posters	Backlit Displays/ frames	Exhibits, Events signs	Vehicle graphic
	■				
Sizes Available	1.37×50M				
Physical Properties	Face film	80um (3.1mil) calendared monomeric			
	Finish	Glossy			
	Whiteness	Clear			
	Gloss/60deg	70-85			
	Elongation at break	70N/mm			
Adhesive Properties	Adhesive Type	Removable Clear			
	Thickness	≥20 micron (≥0.8 mil)			
	Initial Tack (ASTM D882-02)	≥7#			
	Holding (ASTM D882-02)	≥24			
	180° peel strength (ASTM D882-02)	10~12 N/25mm			
Release Liner	Liner weight	120 g/m <sup>2</sup>			
	Liner Type	Single side PE coated silicon paper			
Storage & Application	Shelf Time	60 months			
	Application Temperature	-10 °C to 65 °C			
	Durability	60 Months			
■ FULLY COMPATIBLE					

Graphic Solutions Digital (Pty) Ltd

Head Office  
4 Midhurst Way  
Constantia, 7806

Co. Reg No: 2020/459255/07  
Vat Reg No. 494 015 4919  
Tel: +27 21 794 6094 / 8919