



**5 YR POLYMERIC COLD LAMINATION FILM**

|  |                 |              |         |                       |                  |               |              |                |
|--|-----------------|--------------|---------|-----------------------|------------------|---------------|--------------|----------------|
| <b>DESCRIPTION</b>   |                 |              |         |                       |                  |               |              |                |
| 80mic/3mil super clear polymeric vinyl film, clear solvent resistant acrylic permanent glue, 150gr single PE smooth release liner.   |                 |              |         |                       |                  |               |              |                |
| <b>PROPERTIES</b>  |                 |              |         |                       |                  |               |              |                |
| PARAMETER  |                 |              |         |                       | Value            |               |              |                |
| FILM   | THICKNESS / UM  |              |         | 80um                  |                  |               |              |                |
|  | FINISH          |              |         | GLOSS/MATTE           |                  |               |              |                |
| GLUE   | THICKNESS       |              |         | 20 UM                 |                  |               |              |                |
|  | COLOR           |              |         | Clear permanent       |                  |               |              |                |
| PAPER  | WEIGHT          |              |         | 150 GSM               |                  |               |              |                |
|  | LINER TYPE      |              |         | Single PE paper       |                  |               |              |                |
| AVAILABLE SIZE   |                 |              |         | 1.37m x 50m           |                  |               |              |                |
| SHELF TIME   |                 |              |         | 24 MONTHS             |                  |               |              |                |
| APPLICATION TEMPERATURE  |                 |              |         | -10°C- 65°C           |                  |               |              |                |
| DURABILITY   |                 |              |         | 3 to 5 Years Outdoors |                  |               |              |                |
| <b>APPLICATION</b>   |                 |              |         |                       |                  |               |              |                |
| Banners, Flags   | Large Billboard | POP Displays | Backlit | SIGNS                 | Vehicle Wrapping | Widow Graphic | Arts Graphic | Magnetic signs |
|  |                 |              |         | Y                     | Y                |               |              |                |
| <p>NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.</p> <p>should be submitted within 6 months of receiving the material. 1. Any complaint 2.</p> <p>Avoid washing with aggressive brushes and /or detergents.</p> <p>3. Usage/application should follow the technical guidelines.</p> |                 |              |         |                       |                  |               |              |                |

Graphic Solutions Digital (Pty) Ltd

Head Office  
4 Midhurst Way  
Constantia, 7806

Co. Reg No: 2020/459255/07  
Vat Reg No. 494 015 4919  
Tel: +27 21 794 6094 / 8919