

GraphSol

SELF ADHESIVE VINYL

GraphSol One Way Vision 3 year Removable Adhesive - 3 layer UV Compatible

Specification	Description	
PVC	Type	Calendered monomeric soft PVC film
	Thickness	160±10um
	Color Code	White
	Back	Black coating
	Shrinkage	≤0.8%
	Surface Tension	≥30dn/cm
	Opacity	>99%
	Holes No.	Average 130/sq in
	Hole Diameter	1.5mm
	Distance Between Holes	2.6mm
	Hole Space	30%
Adhesive	Type	Clear solvent based removable pressure sensitive glue
	Thickness	30±2um
	Adhesion Temperature	15°C~40°C
	180°	≥5N/25mm (GB2792-81 China National Standard)
	Peeling Force	
	Initial Adhesion- Ball Tack	≥5# Steel Ball (GB4852-84 China National Standard)
	Holding Power	≥800min (GB4854-84 China National Standard)
	Removable Durability	One year cleanly removable glue on clean glass surface at temperature of 23~25°C and RH of 50~60%
Liner	Type	Laminated Kraft Paper (Additional Liner)
	Color	white
	Weight	210g±10g/m ²
	Release Force	0.4~1N/4cm
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	One way vision media used in digital and silk screen printing machines for signage display, vehicle	
Compatibility of machines and ink	Media is suitable for UV printer and all solvent and eco solvent digital printers with heating system	
	Inks should be the original inks from the printer manufacturers. The best printing temperature is 38-43°C.	
Fire Rating	B2	DIN4102-1
Material Warranty	3 years Outdoors	
UV Resistant	Yes	
Mildew Resistant	Yes	
All above information shall only be used as a guide. Buyers shall independently test and determine the products suitability.		

Graphic Solutions Digital (Pty) Ltd

Head Office
4 Midhurst Way
Constantia, 7806

Co. Reg No: 2020/459255/07
Vat Reg No. 494 015 4919
Tel: +27 21 794 6094 / 8919