



GraphSol One Way Vision - 3 year with Removable adhesive

Specification	Description	
PVC	Type	Calendered monomeric soft PVC film
	Thickness	150±10um
	Color Code	White
	Back	Black coating
	Shrinkage	≤0.8%
	Surface Tension	≥30dn/cm
	Opacity	>99%
	Holes No.	Average 130/sq in
	Hole Diameter	1.6mm
	Distance Between Holes	2.4mm
	Hole Space	41%
	Adhesive	Type
Thickness		30±2um
Adhesion Temperature		15°C~40°C
180° Peeling Force		≥5N/25mm (GB2792-81 China National Standard)
Initial Adhesion- Ball Tack		≥5# Steel Ball (GB4852-84 China National Standard)
Holding Power		≥800min (GB4854-84 China National Standard)
Removable Durability		One year cleanly removable glue on clean glass surface at temperature of 23~25°C and RH of 50~60%
Liner	Type	Laminated Kraft Paper (Additional Liner)
	Color	white
	Weight	140g±5g/m ²
	Release Force	0.4~1N/4cm
Material Warranty	3 years outdoors	
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	One way vision media used in digital and silk screen printing machines for signage display, vehicle graphics ,	
Compatibility of machines and ink	Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki , Roland, Vutek and HP Scitex. Inks should be the original inks from the printer manufacturers. The	
Fire Rating	B2	
UV Resistant	Yes	
Mildew Resistant	Yes	

Graphic Solutions Digital (Pty) Ltd

Head Office
4 Midhurst Way
Constantia, 7806

Co. Reg No: 2020/459255/07
Vat Reg No. 494 015 4919
Tel: +27 21 794 6094 / 8919