



Mesh 270g With Liner

Items	Value	Unit	Test Method
Thickness	0.45	mm	ASTM D-1593
Thickness of PVC Liner	0.8	mm	ASTM D-1593
Weight of PVC Liner	90 +-5	g/sqm	DIN53352
Colour of PVC Liner	White		
Base Fabric	Polyester		DIN60001
Yarn	1000x1000	D	
Construction	12x12	sq.inch	
Weight	270+-10	g/sqm	DIN53352
Weight Tolerance	6.6% difference	g/sqm	
Light Transmittance	37%		GB 2410-80
Wind Permiability	2649%	mm/s	GB/T 5453-1997
Tensile Strength (L)	1500	N/50mm	DIN53354
Tensile Strength (W)	1800	N/50mm	
Tearing Strength (L/W)	450	N/50mm	DIN53363
Tearing Strength (L/W)	500	N/50mm	
Temperature Resistance	-20 ~ + 70	° C	DIN53372
Fire Rating	B2		DIN4102-1
Material Warrantly	6 Months		
UV Resistant	Yes		
Mildew Resitant	Yes		

1. Anti-tearing 1000D yarn, woven by Kaermaye wrap knitting equipment form Germany, doubles its strength and ensure great anti-tearing performance. 2. Good ventilation and lighting. 3. Featured by low cost and easy operation.

All above information shall only be used as a guide. Buyers shall independantly test and determine the products suitability

Graphic Solutions Digital cc

Head Office
4 Midhurst Way
Constantia, 7806

Reg No. CK 1996/003463/23
Vat no. 494 015 4919
Tel: 021 794 6094