



Tarpaulin Panamaflex Coated Media 900gsm

Items	Value	Unit	Test Method
Base Fabric	Polyester		
Yarn	1000x1000	D	
Construction	30x30	/sq.inch	
	12x12	/sq.cm	
Surface Coating	Acrylic lacquering for increased print quality		
Colours	White	Red	Navy Blue
Weight	900	g/sqm	
Weight Tolerance	6.6% difference		
Weight of Fabric	260	g/sqm	
Weight of PVC Coating	640	g/sqm	
Tensile Strength (L/W)	3900/3700	N/5cm	DIN53354 or HG/T2580
Tearing Strength (L/W)	535/480	N	DIN53363 or HG/T2581
Peeling Strength	50	N	DIN53357 or GB8808
Adhesion	90	N/5cm	DIN53357 or GB8808
Temperature Resistance	-30 ~ + 70	° C	DIN53361
Fire Rating	B2		
Material Warranty	1 Year *	Note * Warranty on tarp is restricted to material performing as per strength and peel specs above It does not include any warranties on ink longevity or fading or any glaze adhesion discolouring etc.	
UV Resistant	Yes		
Mildew Resistant	Yes		
Applications	Used as tarpaulin, truck cover, awning, tent, inflatable products, and geotextile.		
All above information shall only be used as a guide. Buyers shall independently test and determine the products suitability			

Graphic Solutions Digital cc

Head Office
 4 Midhurst Way
 Constantia, 7806

Reg No. CK 1996/003463/23
 Vat no. 494 015 4919
 Tel: 021 794 6094